

Adhesive Sealant 1K-PUR K126

- Strong-gripping single-component adhesive and sealant with polyurethane base
- For permanent elastic bonding and sealing
- For primed and coated metals, aluminium, wooden materials, thermosetting plastics
- For car body, container and vehicle construction, ventilation and air-conditioning technology, metal construction, etc.



6630 6500

6630 6501

6630 6502

Artikel-Nr.	Artikel-Bezeichnung	VPE
6630 6500	ADH.SEAL.1K-PUR BK. K126 310ML	ed 24
6630 6501	ADH.SEAL.1K-PUR WH. K126 310ML	ed 24
6630 6502	ADH.SEAL.1K-PUR GR. K126 310ML	ed 24

Replacement nozzle:

- Art. No. 6015 8270

Your Advantage / Benefit

- Can be painted over after around 45 min
- Can be applied with a brush or trowel
- Temperature resistant from -40 °C to +90 °C, briefly up to +120 °C
- Meets the requirements of the German Foods, Consumer Goods and Feedstuffs Code (German Food and Feed Code LFGB)

Application

- Apply the material to the substrate. The coating thickness depends on the composition of the materials to be glued. The counter-material must be laid and pressed on within 10 min. We recommend clamping the bond in place until it hardens completely.
- The surface must be clean, dry, and free from grease
- The adhesion and compatibility with plastics and paints must be tested for the individual objects.



Related Products

- Disposable Gloves Latex FÖRCH Art.-Nr. 5405 210 2 - 4



- Paints AGR 6210

- Curved Flat brush Art.-Nr. 5418 71 5

