


## RED WING 71111 FR COVERALL

 ANTI-STATIC

 FLAME RESISTANT

 ELECTRIC ARC FLASH

 CATEGORY 2

This coverall has a classic look and a great fit, features eight pockets and non-sparking YKK zips throughout. 100% brass press studs are covered on the inside, so no brass comes in contact with your skin. Major seams are double-stitched and stress points are bar-tacked for strength.



### FABRIC

- Flash Guard TM
- Blend 48% Yencel, 39% Modacrylic, 12% Aramid, 1% Carbon
- Finished weight 6.5 oz/yd<sup>2</sup> (220 g/m<sup>2</sup>)
- Weave TWILL 2/1
- NFPA 2112 UL Recognized Component
- CAT2

### COMPLIANCE

EN ISO 11612  
Electric Arc Flash IEC 61482-1-2 Class 1 HRC2 ASTM  
F1959 ATPV 9.1 CAL/CM<sup>2</sup> Anti Static EN1149-5



PROTECTIVE WORKWEAR

## RED WING 61102 DESERT/ TROPICAL FR COVERALL

 ANTI-STATIC

 FLAME RESISTANT

This coverall has a classic look and a great fit. It features eight pockets and non-sparking YKK® zips throughout. 100% brass press studs are covered on the inside, so no brass comes in contact with your skin. Major seams are double- or triple-stitched and stress points are bar-tacked for strength. 2" wide reflective FR striping added for better visibility and safety.



### MATERIAL

Red Wing Flashguard® Duralite™ (Quality 02), FR 93% Meta Aramid/5% Para Aramid/2% Antistat, 4.5 oz/yd<sup>2</sup>/150 g/m<sup>2</sup>

### COMPLIANCE

EN ISO 11612, EN 1149-5, NFPA 2112 UL recognized component -fabric, IEC 61482-2 (Class 1)

