



Climax Lubricants & Equipment Co.

**CLIMAX SPEC SHEET- #800-XH STICK GRADE LUBRICANT/SEALANT
(FMC Part # 3256666)**

DROPPING POINT.....	NON-DROPPING
BASE OIL.....	SYNTHETIC, POLYEMERIZED HYDROCARBON DERIVATIVE
SHELF LIFE.....	INDEFINITE
OXIDATION STABILITY.....	GOOD
TEMPERATURE RANGE.....	-20 DEG.F.TO +500 DEG.F.
PENETRATION.....	NLGI GRADE #6 (ASTM 85-115)
THICKENER.....	INORGANIC
FILLER.....	RHEOLOGICAL ADDITIVE
COLOR.....	BROWN

NON TOXIC-HAZARDOUS MATERIAL
FLASH POINT ABOVE 400 DEG.F.
NON FLAMMABLE
Manufactured/Country of Origin – U.S.A.

This Sealant is formulated particularly for use in straight bodied or tapered plug valves and exhibits excellent tack and adhesion. This product offers excellent resistance to aliphatic hydrocarbon liquids and gases, crude distillates, fuel and lubricating oils, sweet or sour gas, kerosene, gasoline, aqueous solutions and water. (Not suitable for caustic or amine services.)

Stephen D. Frauenberger, President - Sales/Manufacturing
Email: sales@climaxlube.com
Climax Lubricants & Equipment Co. – U.S.A.

**P.O. Box 5235 – Houston, Texas U.S.A. 77262-5235 – 7915 East Elm Street – 77012
713-923-2626 – Fax 713-928-9025 - climaxlube@aol.com**