

MOUNTAINS SAFETY SHOES

Model	Standard	Category
SD 3040	EN ISO 20345: 2011	S3



Size : 39 to 46.

Steel Toe W / H (high and wide), resistant to impact 200 joules.

Characteristics Dielectric footwear. Meets ASTM 2413

User Instructions & Storage

- 1. RECOMMENDED TO USE:** Basic workplaces, Construction, Logistics, Mechanics, Glasses installation, Workshop, Farming, Garden, Car repair shop etc.
- 2. LIMITATION TO USE:** It is very important that footwear selected must be suitable for the right workplaces. The protection against risks or hazards which are not mentioned in this document is not warranted.
- 3. FITTING & SIZE:** All footwear are marked with standard size on tongue label. Some with different size comparison, such as EU size, US size, UK size etc. Please wear footwear by a suitable size. Footwear which are too loose or too tight may not provide optimum level of protection.
- 4. STORAGE:** Keep in its original packaging, under ordinary temperature and non-humidity conditions and in clean, covered and ventilated premises.
- 5. CLEANING:** Clean footwear regularly by high quality cleaning treatments recommended as suitable for the purpose. Don't use caustic or corrosive cleaning agents.

Material:

Manufacturing Direct injection to the cut.

embossed leather

Color Black.

Full lining in breathable textile.

Padded ankle brace with high-density foam.

Double seams with rot-resistant T-20 Nylon thread.

1.6mm Thermoformed Buttress.

Interchangeable interior plate.

Assembly template Non-woven material.

Non-perforating steel insole, resistant to

1,100 N drilling.

Double density polyurethane plant, resistant to derivatives of hydrocarbons, non-slip characteristics.

High resistance plastic mesh fabric. Reinforced heel.